

Meet Our Table Mounts








TABLE STANDS <i>Transportable, height-adjustable and standing stable on even or uneven surfaces.</i>	TS-XL	TS-GO	TS-DC	TS-UC	TS-FT	TS-AT
						
FEATURES						
Method of Device Position Adjustment	QuickShift levers	Quickshift levers	QuickShift levers	Quickshift levers	Hinged for multiple angles Lockable hinge joint	Quickshift leavers
Device Height	Up to 52cm	Up to 50cm	Up to 24cm	Up to 18cm	N/A	Up to 20cm
Load Capacity	7.5kg	7.5kg	2.5kg	2.5kg	N/A	7.5kg
Weight	1.15kg	1.4kg	0.6kg	0.56kg	0.345kg	1kg
Pricing per website:	TS-XL - Link Assistive	TS-GO - Link Assistive	TS-DC - Link Assistive	TS-UC - Link Assistive	TS-FT - Link Assistive	TS-AT - Link Assistive
Other Notes	Ideal for eye gaze devices Levelling mechanism	Comes with carry bag Ideal for transitions between different sites	Ideal for touch devices Folds flat	Ideal for touch devices Folds flat SLS version	Width of device holder 25mm and 10mm Highly transportable	Ideal for uneven surfaces Folds flat
All Rehadapt products are compliant with the ISO 14971:2019 Standard. Declarations of Conformity are in place for all products. Rehadapt is ISO certified (23 March 2021). ISO Norm: DIN EN ISO 13485. All mounts come with 2 years warranty.						














TABLE CLAMPS M3D <i>Sturdy and adjustable options that save space on a desk/table surface.</i>	ClampOnMount	TC	ClampOnMount Dual SC
			
FEATURES			
Method of Device Position Adjustment	QuickShift levers	QuickShift levers	QuickShift levers
Device Height	Up to 80cm	Up to 27.5cm	Up to 72cm
Load Capacity	5.4kg	5.4kg	5.4kg
Weight	1.57kg	1.08kg	2kg
Pricing per website:	ClampOnMount - Link Assistive	Table Clamp Mount - Link Assistive	ClampOnMount-Dual-SC - Link Assistive
Other Notes	Two tube system for greater height and flexibility	Single tube system	Ideal for corner mounting Base width up to 40cm
<i>All Rehadapt products are compliant with the ISO 14971:2019 Standard. Declarations of Conformity are in place for all products. Rehadapt is ISO certified (23 March 2021). ISO Norm: DIN EN ISO 13485. All mounts come with 2 years warranty.</i>			

TABLE CLAMPS <i>Floating (OneHand)</i> Keeps devices “floating” for easy repositioning. Device can be moved 90° vertically and 360° horizontally.	TC-OH	TC-OH-HD	TC-OH Light
			
FEATURES			
Method of Device Position Adjustment	One-hand floating mechanism	One-hand floating mechanism	One-hand floating mechanism
Device Height	-20-20cm	-20-20cm	-20-20cm
Load Capacity	2-6kg	6-11kg	0.7-3kg
Weight	3.15kg	3.15kg	3.15kg
Pricing per website:	TC-OH - Link Assistive	TC-OH-HD - Link Assistive	TC-OH Light - Link Assistive
All Rehadapt products are compliant with the ISO 14971:2019 Standard. Declarations of Conformity are in place for all products. Rehadapt is ISO certified (23 March 2021). ISO Norm: DIN EN ISO 13485. All mounts come with 2 years warranty.			

<div>TABLE CLAMPS</div> <div>L3D</div> <div>Sturdy and adjustable options for smaller, lightweight devices.</div> <div></div>	<div>TC FM UDS/SLS</div> <div></div>	<div>TC L3D 1QS UDS/SLS</div> <div></div>	<div>TC L3D 2QS UDS/SLS</div> <div></div>	<div>TC L3D 3QS UDS/SLS</div> <div></div>
FEATURES				
Method of Device Position Adjustment	Gooseneck QuickShift Lever	QuickShift Lever	QuickShift Levers	QuickShift Levers
Device Height	Up to 35cm	Up to 30cm	Up to 55cm	Up to 75cm
Load Capacity	1.2kg	1.2kg	1.2kg	1.2kg
Weight	1.05kg (UDS) 0.95 kg (SLS)	0.95kg (UDS) 0.74kg (SLS)	1.15kg (UDS) 0.94kg (SLS)	1.47kg (UDS) 1.28kg (SLS)
Pricing per website:	TC L3D FM - Link Assistive	Light 3D Table Clamps - Link Assistive		
All Rehadapt products are compliant with the ISO 14971:2019 Standard. Declarations of Conformity are in place for all products. Rehadapt is ISO certified (23 March 2021). ISO Norm: DIN EN ISO 13485. All mounts come with 2 years warranty.				

